

Galanz
AIR CONDITIONERS



Our Service is second to none... and we can PROVE it!!

Ultimate in Design Quality & Efficiency



Arcus series

Seer A++ • Eco Friendly • 5 Year Warranty •  **FULL DC INVERTER TECHNOLOGY**



Triq Guzepp Xuereb ix-Xhudi Swatar
Tel: 27234567 , 21234755
www.clima755.com
Email: sales@clima755.com

Find us on Facebook <https://www.facebook.com/Clima755>



New Specifications

Model			AUS- 12H53R150L71(Ze2)	AUS- 18H53R120D71(Za5)
Power supply		Ph-V-Hz	1Ph / 220-240V/50HZ	1Ph-220-240V~50Hz
Cooling	Capacity	W	3550(600~4100)	4800(2000-5500)
	Input	W	1050(65~1430)	1600(320~2060)
	Rated current	A	4.80(0.6~6.8)	7.1(1.9~9.2)
	SEER		6.62	6.00
Heating	Capacity	W	3800(700~5100)	5200(800~5500)
	Input	W	1050(120~1700)	1730(140~2300)
	Rated current	A	4.80(0.9~7.5)	7.8(0.8~10.4)
	SCOP		3.80	3.95
Max. input		W	2000.00	2400
Max. current		A	10.5	11
Starting current		A	/	/
Compressor	Type		ROTARY	ROTARY
	Brand		PANASONIC	Hitachi
Indoor Unit	Indoor air flow	m3/h	500/450/380	850/750/650/600
	Rated input	W	20	40
	Rated current	A	0.2	0.28
	Moisture Removal	(L/h)	1.2	2.2
	Sound power level	dB(A)	34/37/40	37/40/43
	Unit dimension	mm	805x290x210	860x292x205
	Packing (W*H*D)	mm	870X365X280	930X365X280
	Net weight	Kg	11	11
	Gross weight	Kg	12.5	13
Outdoor Unit	Sound power level	dB(A)	51	51
	Unit dimension	mm	745x552x328	830x530x320
	Packing (W*H*D)	mm	800x605x370	910X620X380
	Net weight	Kg	30	41
	Gross weight	Kg	33.5	44.5
	Refrigerant type		R410A	R410A
	Refrigerant charge	g	950	1200
Design pressure	MPa	4.1	4.1	
Refrigerant pipe	Liquid side	mm	6.35	6.35
	Gas side	mm	12.7	12.7
	Max. refrigerant pipe length	m	10	10
	Max. difference in level	m	5	5
Operation temperature		℃	-10~43	-7~43
Ambient temperature		℃	-15~48	-15~48
Application area		m2	14-21	15-30

The above design and specifications might be changed without prior notice for product improvement.