

Split Air Conditioner

HIRO series



FEATURES



SPECIFICATIONS

MODEL	INDOOR	HTN-12IV	HTN-17IV	HTN-21IV
	OUTDOOR	HTG-12IV	HTG-17IV	HTG-21IV
COOLING CAPACITY		11,000 BTU 3.22 kW (0.60-3.81)	15,700 BTU 4.60 kW (0.64-5.22)	21,000 BTU 6.15 kW (1.75-6.3)
HEATING CAPACITY		11,600 BTU 3.40 kW (0.60-3.81)	17,100 BTU 5.01 kW (0.70-5.28)	21,150 BTU 6.20 kW (1.75-6.76)
COOLING	SEER	6.1	6.1	6.5
	COOLING	A++	A++	A++
HEATING	Average Zone	SCOP	4.0	4.0
		ENERGY	A+	A+
	Warmer Zone	SCOP	5.1	5.1
		ENERGY	A+++	A+++
POWER SOURCE		220-240V, 50Hz		
DEHUMIDIFYING CAPACITY		1.4 L / h	1.8 L / h	2.4 L / h
INDOOR SOUND LEVEL		29/35/37/42	33/37/41/45	34/39/43/47
OUTDOOR SOUND LEVEL		51	54	57
COMPRESSOR		Rotary		
REFRIGERANT		R410		
DIMENSIONS (W x H x D)	INDOOR	790x275x200	970x300x224	970x300x224
	OUTDOOR	842x596x320	842x596x320	955x700x396
WEIGHT	INDOOR	9	13.5	13.5
	OUTDOOR	31	33.5	46
Refrigerant Pipe Max length		20	20	25
Ref. Pipe Max difference in level		10	10	10

Characteristics

Auto Restart	Smooth Start	Light Function
Turbo Function	Autodiagnose	Smart Preheating
Autoclean	Smart Defrosting	Dehumidifier



Triq Guzepp Xuereb ix-Xhudi, Swatar

Tel: 27234567 | email: sales@clima755.com | web: www.clima755.com

